

In the Title:

Please change the Title of the present application to "LEADLESS
SEMICONDUCTOR PACKAGE WITH STANDOFF".

6'

In the Specification:

Please amend the paragraph beginning on page 1, line 4, and ending on page 1, line 7, as follows:

B² The present invention relates to a semiconductor package; and, more specifically, to a method of forming an HSQFN (High Stand-off Quad Flat Non-leaded) type package.

Please amend the paragraph beginning on page 1, line 10 and ending on page 2, line 5, as follows:

B³ Integrated circuits industry and fabrication involve the formation of semiconductor wafers, integrated circuits and chip ~~package~~ packages. With the advent of Ultra Large Scale Integrated (ULSI) ~~circuits~~ circuit technologies, it has been a trend to scale down the ~~geometry~~ geometric dimension dimensions of semiconductor devices and increase the density of semiconductor devices per unit area of silicon wafer. Thus, the sizes of devices, such as memory cells, have gotten smaller and smaller such that the area available for a single device has become very small. Further, the manufacturers of the devices are striving to reduce the sizes of such devices while simultaneously increasing their speed. The renewed interest in high density ~~hybrid~~ hybrids is driven by the requirement to handle large numbers of IC interconnections, the increasing clock rate of digital systems and the desire to pack greater functionality into smaller spaces. Therefore, the number of a package's leads becomes more and more. An issue is that the package must have the capability ~~to spread~~ of spreading the heat generated by the die, efficiently.

Please amend the paragraph beginning on page 2, line 6, and ending on page 2, line 16, as follows:

B⁴ For assembling a semiconductor device, a semiconductor chip is properly positioned against the lead frame thus formed, then attached to the insulating film by heat and pressure. Next, the inner leads and their corresponding contact pads are electrically connected by bonding wires using a bonding tool, ~~respectively~~. Finally, the inner leads

B⁴ and the semiconductor chip are covered by a molding resin to ~~expose~~ such that the outer leads of the lead frame ~~from~~ are exposed in the molding resin.

Please amend the paragraph beginning on page 2, line 17, and ending on page 3, line 6, as follows:

B⁵ United States Patent 6,118,173 to Emoto, entitled "Lead frame and a semiconductor device". The package includes a chip, inner leads ~~reaches~~ reaching the periphery of the semiconductor chip, and bonding wires for electrically connecting the semiconductor chip and the inner leads. The semiconductor chip is fixed on a die pad portion, and a chip fixing inner lead is integrated with the die pad portion. To simplify the bonding wire connection process and improve ~~the~~ its reliability, the chip fixing inner lead has a step portion so that the die pad portion is formed at a lower position than the inner leads. Further, United States Patent 6,107,675 disclosed a lead frame structure.

Please amend the paragraph beginning on page 3, line 7, and ending on page 3, line 18, as follows:

B⁶ One of the package types is ~~so~~ called QFP (Quad flat package), ~~the~~ Such QFP package is the type used in logic and microprocessor packing that requires up to approximately ~~hundreds~~ one hundred pins. The semiconductor memory devices are designed to comprise terminals (leads) for external connection which are as short as possible in order to make it possible to operate the devices at a higher speed such as that of the QFN (Quad Flat Non-leaded package). The QFN has a high-speed-oriented package structure in which no leads are provided but electrode pads for soldering are provided to a resin package.

Please amend the paragraph beginning on page 3, line 21, and ending on page 3, line 23, as follows:

B⁷ The object of the present invention is to provide a package with easier ~~process~~ processing and improved thermal dissipation.

Please amend the paragraph beginning on page 3, line 24, and ending on page 4, line 12, as follows:

B8 A method of forming a an HSQFN (High Stand-off Quad Flat Non-leded) package comprising ~~Providing~~ providing a leadframe with bonding pads and die pads for receiving a die. Then, the die is attached on the die pad and bonding wires are connected between the bonding pads and the die for electrical connection. A molding process is used to encompass the die by with a compound from a first surface of the leadframe. Then, backside etching is used ~~to the leadframe from~~ on a second surface of the leadframe to expose a lower surface of the compound, thereby separating the bonding pads and the die pads. A ~~sigulation~~ singulation process is ~~applied~~ used to separate each individual package by cutting the leadframe and the compound.

Please amend the paragraph beginning on page 4, line 15, and ending on page 4, line 17, as follows:

B9 FIGURE 1 is a cross section view of a step of forming a die pad and bonding pad according to the present invention.

Please amend the paragraph beginning on page 4, line 19, and ending on page 4, line 21, as follows:

B10 FIGURE 2 is a cross section view of a step of bonding a die on a die pad according to the present invention.

Please amend the paragraph beginning on page 5, line 7, and ending on page 6, line 6, as follows:

B11 The present invention discloses a method for manufacturing a High Stand-off Quad Flat Non-leded package ~~technology~~. A package in accordance with the invention will be described in conjunction with ~~and~~ an illustrative embodiment of the invention. ~~Please referring~~ Referring to FIGURE 6, the structure of the HSQFN (High Stand-off Quad Flat Non-leded) package includes a leadframe having a die pad 62 and bonding pads 60. The die pad 62 and bonding pads 60 are ~~the~~ portions of the leadframe. ~~The several die pad 62 straightly elongated in parallel relationship to each other from the~~

B¹¹
~~frame body~~. The die pad 62 is designed to carry the die 64 ~~adhesively thereon~~ **attached thereto** by adhesive material 63. A number of bonding pads 60 is formed on the lower surface of the package, and the die 66 is connected to the bonding pads 60 of the lead frame via a plurality of bonding wires 68 for electrical communication. Molding compound 70 encompasses the entire die 66, the bonding wire 68 and the major portion of the lead frame, leaving the terminal of the inner lead exposed out of the body. According to the structure of the present invention, not only the die pad is exposed, but also the lower surface of the bonding pad 60 is exposed. This structure provides excellent ~~60~~ thermal dissipation from the packages.

Please amend the paragraph beginning on page 6, line 8, and ending on page 6, line 18, as follows:

B¹²
Two stages of etching are used to etch the upper surface (first side) and lower surface (second surface), respectively. The method comprises performing die bonding, wire bonding and molding between two stages of etching. ~~Wherein a~~ **The** first etching of the two stages of etching comprises forming an inward indentation portion of the leadframe from a first side of said leadframe to define die pads and bonding pads. A second etching of the two stages of etching comprises separating the die pads and bonding pads by etching from a second side of the leadframe.

Please amend the paragraph beginning on page 6, line 20, and ending on page 7, line 4, as follows:

B¹³
The method for forming the package includes preparing a lead frame having a die pad 62 to receive a die 64, as shown in FIGURE 1. This present invention can be achieved by using "stand off" method. In one preferred embodiment, ~~please refer to~~ **as shown in** FIGURE 1, the upper surface (the first ~~surface~~ **side**) of the lead frame is etched to form a plurality of inward indentation portions 61. Alternatively, the inward indentation portions 61 may be formed by **an** external force punch.

Please amend the paragraph beginning on page 7, line 5, and ending on page 7, line 14, as follows:

B¹⁴
Next, the die 64 is bonded on the die pad 62 by adhesive material such as silver epoxy 63, as shown in FIGURE 2. Subsequently, bonding wires 68 are bonded to connect the die 66 and the connecting pads or bonding pads 60, as illustrated in FIGURE 3. Preferably, a wire bonding technique is carried out to form the bonding wires for constructing the communication path between the die 66 and the external circuits. As the bonding technique is well known in the art, the detailed description thereof is omitted.

Please amend the paragraph beginning on page 7, line 16, and ending on page 8, line 6, as follows:

B¹⁵
Turning to ~~FIGURE~~ **FIGURE** 4, the die is encapsulated by mold resin 70. To phrase in another way, molding compound is injected into a mold to form a shielding shield to protect the die 64 from being damaged by external force. Please turn to FIGURE 5, thereafter, a PMC (post molding curing) step is performed; as this is well known in the art, a detailed description is unnecessary. Next, a backside etch is utilized to separate the connection between the die pads 62 and the bonding pads 60. This can be achieved by using lithography and etching ~~process~~ processes to etch the leadframe from the second surface of the leadframe, thereby exposing the lower surface of the mold resin 70. Other ~~method~~ methods may be used, as shown in FIGURE 5. The etched portions of the ~~leadfram~~ leadframe are aligned to the inward indentation portions of the first surface.

Please amend the paragraph beginning on page 8, line 8, and ending on page 8, line 12, as follows:

B¹⁶
Referring to FIGURE 6, a ~~sigulation~~ singulation step is performed to separate each individual package. Therefore, the package is cut at specific portions. Optionally, solder ball may be formed on the terminal of the bonding pads.

Please amend the paragraph beginning on page 8, line 14, and ending on page 8, line 17, as follows:

B¹⁷
The benefits of the present invention ~~includes~~ include the improvement of its heat dissipation characteristic. The die pad which is a portion of the leadframe is exposed to enhance the thermal dissipation.

Please amend the paragraph beginning on page 8, line 19, and ending on page 9, line 7, as follows:

818
As is understood by a person skilled in the art, the foregoing preferred embodiments of the present invention are ~~illustrated~~ illustrative of the present invention rather than limiting of the present invention. It is intended to cover various modifications and similar arrangements included within the spirit and scope of the appended claims, the scope of which should be accorded the broadest interpretation so as to encompass all such modifications and similar ~~structure~~ structures. Thus, while the preferred embodiment of the invention has been illustrated and described, it will be appreciated that various changes can be made therein without departing from the spirit and scope of the invention.